

# VYBO Electric a.s.



## Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	1LC-315S-8 55KW 400/690V 50HZ
Brand	VYBO Electric

### Identification

Type:	1LC-315S-8	Frame:	315	mm	
Power:	55 kW	Poles:	8	P	
Rated Current:	380 V	111	Rated Voltage:	400 / 690	
	400 V	106		Connection:	Δ/Y
	415 V	102			Insulation Class:
Speed:	735	rpm	Temperature Rise:		
Frequency:	50	Hz	Service Factor:	1,0	
Direct on line starting torque ratio (LRT/RLT):	1,8		Duty:	S1, S2, S3, S4-S9	
Direct on line pull out torque ratio (BDT/RLT):	2		Ambient Temperature:	-35~50°C (On request possible 62°C)	
Direct on line starting current ratio (LRA/RLA):	6,6		Altitude:	1000m	
Efficiency:	92,8	%	Protection Degree:	IP55	
Power factor:	0,81		Cooling:	IC411	
Noise level:	82	dB(A)	Mounting:	IM B (On request)	
Weight:	852	kg	Vibration:	2.8 mm/s	
Rotor inertia:	4,79	kg/m <sup>2</sup>	Direction of Rotation:	Both	
			Starting Method:	DOL or VFD	
			Coupling:	DIRECT	
			Load Type:	Parabolic or linear curve	
			Terminal box:	2xM63X1.5	



### Bearing Information

	DE	NDE
Bearing:	NU319C3	6319C3
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

	VYBO Electric		Customer

### Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

### Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date