

VYBO Electric a.s.



Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	2AL-90L-6 1,1KW 230/400V 50HZ
Brand	VYBO Electric

Identification

Type:	2AL-90L-6	Frame:	90	mm
Power:	1,1 kW	Poles:	6	P
Rated Current:	400 V 2,8 A	Rated Voltage:	230 / 400	V
Speed:	930 rpm	Connection:	Δ/Y	
Frequency:	50 Hz	Insulation Class:	F	
Direct on line starting torque ratio (LRT/RLT):	2	Temperature Rise:		
Direct on line pull out torque ratio (BDT/RLT):	2,1	Service Factor:	1,0	
Direct on line starting current ratio (LRA/RLA):	5,9	Duty:	S1, S2, S3, S4-S9	
Efficiency:	78,1 %	Ambient Temperature:	-35 ~ 50°C (On request possible 62°C)	
Power factor:	0,72	Altitude:	1000m	
Noise level:	57 dB(A)	Protection Degree:	IP55	
		Cooling:	IC411	
		Mounting:	IM B (On request)	
		Vibration:	2.8 mm/s	
		Direction of Rotation:	Both	
		Starting Method:	DOL or VFD	
		Coupling:	DIRECT	
		Load Type:	Parabolic or linear curve	
		Terminal box:	2-M25X1.5	



Bearing Information

	DE	NDE
Bearing:	6205-2RZ	6205-2RZ
Regreasing int.(h):		
Grease amount(g):		
Grease:		

Notes / Accessories

Deviation Sheet

	VYBO Electric	Customer

Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date