

# VYBO Electric a.s.



## Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	4LC-225M-2 45KW 400/690V 50HZ
Brand	VYBO Electric

### Identification

Type:	4LC-225M-2	Frame:	225	mm
Power:	45 kW	Poles:	2	P
Rated Current:	380 V	A	Rated Voltage:	400 / 690 V
	400 V		Connection:	Δ/Y
	415 V		Insulation Class:	F
Speed:	2975 rpm	Temperature Rise:		
Frequency:	50 Hz	Service Factor:	1,0	
Direct on line starting torque ratio (LRT/RLT):	2	Duty:	S1, S2, S3, S4-S9	
Direct on line pull out torque ratio (BDT/RLT):	2,3	Ambient Temperature:	-35~50°C	
Direct on line starting current ratio (LRA/RLA):	9	Altitude:	1000m	
Efficiency:	95 %	Protection Degree:	IP55	
Power factor:	0,89	Cooling:	IC411	
Noise level:	86 dB(A)	Mounting:	IM B (On request)	
Weight:	366 kg	Vibration:	2.8 mm/s	
Rotor inertia:	0,34021 kg/m <sup>2</sup>	Direction of Rotation:	Both	
		Starting Method:	DOL or VFD	
		Coupling:	DIRECT	
		Load Type:	Parabolic or linear curve	
		Terminal box:	2-M50X1.5	



### Bearing Information

	DE	NDE
Bearing:	6313C3	6313C3
Regreasing int.(h):		
Grease amount(g):		
Grease:		

### Notes / Accessories

### Deviation Sheet

	VYBO Electric		Customer

### Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

### Edition

Performed	Checked	Date



Item	Changes	Performed	Checked	Date